




6765106082



**Socket outlet with earthing pin and LED orientation light enhanced contact protection, Screw-in lift terminals**

Technical features

**Architecture**

- 2pole + earth

**Main electrical features**

Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

**Power**

Power consumption	0.25 W/0.35 VA
-------------------	----------------

**Detection**

- integrated brightness sensor that switches the orientation light on at twilight and off when there is sufficient brightness

**Materials**

Colour of design line	white
-----------------------	-------

**Lighting control**

Switch-off brightness	≈ 4 lx
Switch-on brightness	≈ 2 lx
Light intensity (white)	0,2 cd

**LED control**

LED	long service life of the LED, white LED light
-----	---

**Connection**

Conductor cross-section (rigid)	max. 2,5 mm <sup>2</sup>
Connection terminals	according to IEC 60884-1
- with screw-in lift terminals	

**Cable**

- through-wiring possible, therefore also ideal for retrofitting

**Equipment**

- additional benefit by combination of a socket outlet with an orientation light

**Use**

Differentiation characteristic 2 - Sales	enhanced contact protection
Differentiation characteristic 3 - Sales	Screw-in lift terminals

---

**Safety**

---

IK protection code against mechanical impacts	05
Enhanced contact protection	according to IEC 60884-1
- Enhanced contact protection	

---

**Identification**

---

Secondary design line(s)	Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9
--------------------------	--

---

**Instructions**

---

Information text	<b>Caution!</b> Items with special flush-mounted insert. Centre plates with LED orientation lights are not compatible with the standard socket outlets.
------------------	--

---