



85801100



IP20

quicklink

## KNX radio brightness sensor Electronics platform, polar white matt

### Technical features

#### Functions

- ETS additional functions: button function, battery condition
- reset function (to factory setting)
- quicklink functions: up/down push-button

#### Configuration

- confectioned, with fibre-optic cable and plug

#### Controls and indicators

- with configuration button

#### Connectivity

Radio protocol	KNX Radio
Receiver category	2

#### Frequency

Radio transmission frequency	868,3 MHz
------------------------------	-----------

#### Power

Radio transmission power	< 10 mW
--------------------------	---------

#### Measurement

Relative humidity (without condensation)	0...65 % (without condensation)
--	---------------------------------

#### Battery

Battery service life [years]	≈ 4
------------------------------	-----

- with 2 Micro, alkaline batteries AAA LR03

#### Detection

Fibre optic cable, sensor cable length	≈ 1,5 m
--	---------

#### Materials

Colour of design line	polar white
RAL colour	RAL 9010 - Pure white
Surface appearance	matt

#### Dimensions

Length	138 mm
Height	126 mm
Width	31 mm

#### Lighting control

Twilight setting range	≈ 10...300 lx
Sun setting range	≈ 1...10 klx

### LED control

LED	with 2 potentiometers for sun/twilight and LED display for actual value, with configuration LED
-----	---

### Installation, mounting

Installation mode	for suction cover to window pane
-------------------	----------------------------------

### Connection

- integration in the KNX radio/TP gateway, surface-mounted, into the KNX TP system

### Cable

Cable length, reed contact	max. 3 m
----------------------------	----------

### Settings

- toolless quicklink configuration using buttons and LED display

### Scope of delivery

- with adhesive pads and adhesive cable clips for fastening
- with photodiode

### Equipment

Number of radio channels	1
Number of quicklink links	max. 20 transmitter/receiver
Transmitter duty cycle	1 %

### Use conditions

Operating temperature	0...50 °C
- low intrinsic energy requirement	

### Weight

Weight	≈ 70 g
--------	--------

### Identification

Application, usage	KNX radio- sensors
Main design line	Electronics platform