



85265100



quicklink

## KNX radio blind actuator 1gang surface-mounted Electronics platform, white

### Technical features

#### Architecture

Bus system	KNX
------------	-----

#### Functions

Bus module detachable	no
-----------------------	----

- ETS additional functions: +6 scenes, operating mode, status display, 2 x alarm
- Repeat function can be activated to increase the radio range
- reset function (to factory setting)
- scene saving lockable
- scene opening via KNX radio appliances
- quicklink functions: blind, 2 scenes, forced control, up/down push-button

#### Configuration

- with 2 mechanically and electrically mutually-locked relay contacts

#### Controls and indicators

- with manual operation up/down
- with configuration and function button

#### Connectivity

Bus system radio frequent	no
Bus system LON	no
Bus system Powernet	no
Radio protocol	KNX Radio
Receiver category	2

#### Main electrical features

Frequency	50 Hz
-----------	-------

#### Electric current

Input signal current	33 µA
Switching current	10 A /230 V AC1

#### Frequency

Radio reception frequency	868,3 MHz
---------------------------	-----------

#### Measurement

Relative humidity (without condensation)	0...65 % (without condensation)
--	---------------------------------

#### Materials

Colour independent of design lines	white
------------------------------------	-------

#### Dimensions

Length	150 mm
Height	150 mm
Width	85 mm

### LED control

---

LED	with configuration and function LEDs, with control LED (relay closed)
-----	---

---

### Connection

- 
- with screw-in lift terminals
  - integration in the KNX radio/TP gateway, surface-mounted, into the KNX TP system
- 

### Cable

- 
- with mounting plates and strain reliefs
- 

### Settings

---

Lamella adjustment on signal duration	< 1 s
---------------------------------------	-------

---

- toolless quicklink configuration using buttons and LED display

---

### Equipment

---

Number of quicklink links	max. 20 transmitter/receiver
Self-retaining for 2 min on signal length	> 1 s
Transmitter duty cycle	1 %
Change-over time for change of direction	< 0,6 s

---

### Use conditions

---

Operating temperature	-10...55 °C
-----------------------	-------------

---

- low intrinsic energy requirement

---

### Identification

---

Application, usage	KNX radio - actuators
Product family	product family: output
Main design line	Electronics platform

---