



4587



FCC socket outlet 8/8pole shielded, cat.6 iso Communication technology

Technical features

Architecture

Design to according to DIN EN 60603-7-51

Connectivity

- with 45° oblique outlet
- for RJ11, RJ12 and RJ45 plugs

Main electrical features

Rated voltage 72 V DC
Rated current 0,5 A

Voltage

- suitable for PoE+

Frequency

Transmission bandwidth max. 500 MHz

Resistance

Shield contact resistance 100 mΩ
Signal contact resistance 20 mΩ

Materials

Colour code A and B according to TIA/EIA-568-B.2
- Housing made of die-cast zinc

Dimensions

Insertion depth 31 mm

Installation, mounting

Installation mode without spreader claws, screw fastening via supporting plate

Connection

- with LSA + terminals
- with screen contacting 360° and strain relief

Cable

Conductor Ø 0,4...0,63 mm
- flexible cable routing

Equipment

- external eyelets on the supporting ring can be broken off for round designs

Safety

Cat.6(\sub A) iso, Class E(\sub A), shielded	according to ISO/IEC 11801 A2
Protective screen	according to DIN EN 55022, Class B
Protection index IP	IP20
- No	

Use conditions

Operating temperature	-40...70 °C
-----------------------	-------------

Weight

Weight	≈ 169 g
--------	---------

Identification

Application, usage	Communication technology
Main design line	Communication technology
