



## Touch Panel 7" Android KNX, anthracite

### Technical features

#### Architecture

Fixing mode flush-mounting

#### Functions

Touch function yes

- multi-touch function for the connection of multiple actions, e.g. to activate a function with simultaneous setting of a function value

#### Configuration

- RJ45 Port for LAN connection

#### Controls and indicators

- depending on the software visualisation one and two surface operation, stepless configuration based on sliding and page scrolling by swiping are supported
- suitable for horizontal domovea visualisation
- signal and operating panel with touch-sensitive, capacitive TFT colour display in 16:9 format, with Multi touch operation
- for visualisation of domovea software and display of preconfigured functions, measured values and data

#### Connectivity

Connection RJ45 cable in scope of delivery

Ethernet data rate 10/100 Mbit/s

Interface Connection to KNX system via domovea server

- with USB/Mini USB type A adapter cable
- with RJ45 connector kit from connector and patch cable

#### Voltage

Auxiliary voltage 18...48 V DC

Power over Ethernet (PoE) 18...48 V DC

#### Power

Power consumption < 10 W

#### Measurement

Relative humidity (without condensation) 10...90 %

#### Screen

Resolution graphical display 800 x 480 px

TFT screen size 7 "

Display yes

#### Storage

RAM 512 MB

75740107



IP20

### Materials

RAL colour	RAL 7016 - Anthracite grey
Material	glass
Material family	Glass

### Dimensions

Assembling height	12 mm
-------------------	-------

### Installation, mounting

Installation mode	for flush-mounted and hollow-wall mounting, for vertical and horizontal mounting
-------------------	--

### Connection

Conductor cross-section (flexible), with wire end sleeve	0,75 mm <sup>2</sup>
Conductor cross-section (rigid)	1,5 mm <sup>2</sup>
Connection	Mini-USB 2.0 jack e.g. for external storage media or updates on the upper display edge is accessible without dismantling, 2 USB 2.0 connections on the rear

### Settings

Supported configuration modes	system, easy
-------------------------------	--------------

### Scope of delivery

- Microphone and loudspeaker with echo suppression

### Equipment

Interface type	Ethernet
Text field	no
Light intensity	300 cd/m <sup>2</sup>
Processor	1 GHz

- Display illumination can be switched on automatically using brightness sensor
- silent, long-lasting convection cooling without fan
- card slot with 8 GB SDHC card

### Standards

General standards	EN 55022, EN 55024, EN 60950-1
-------------------	--------------------------------

### Software

- Operating system: OS Android 4.1
- Applications (Apps) available in preinstalled Android launcher - without acces to external apps
- Integration of door communication functions in the domovea client or Elcom VideoFON client

### Safety

Protection index IP	IP20
---------------------	------

### Use conditions

Operating temperature	5...45 °C
Storage/transport temperature	-20...60 °C

**Identification**

---

Composition	Control element
Main design line	KNX

---