



## Touch Panel 7" Android KNX, anthracite

### Technical features

#### Architecture

Fixing mode	flush-mounting
-------------	----------------

#### Functions

Touch function	yes
----------------	-----

- multi-touch function for the connection of multiple actions, e.g. to activate a function with simultaneous setting of a function value

#### Configuration

- RJ45 Port for LAN connection

#### Controls and indicators

- depending on the software visualisation one and two surface operation, stepless configuration based on sliding and page scrolling by swiping are supported
- suitable for horizontal domovea visualisation
- signal and operating panel with touch-sensitive, capacitive TFT colour display in 16:9 format, with Multi touch operation
- for visualisation of domovea software and display of preconfigured functions, measured values and data

#### Connectivity

Connection	RJ45 cable in scope of delivery
Ethernet data rate	10/100 Mbit/s
Interface	Connection to KNX system via domovea server
<ul style="list-style-type: none"> <li>- with USB/Mini USB type A adapter cable</li> <li>- with RJ45 connector kit from connector and patch cable</li> </ul>	

#### Voltage

Auxiliary voltage	18...48 V DC
Power over Ethernet (PoE)	18...48 V DC

#### Power

Power consumption	< 10 W
-------------------	--------

#### Measurement

Relative humidity (without condensation)	10...90 %
--	-----------

#### Screen

Resolution graphical display	800 x 480 px
TFT screen size	7 "
Display	yes

#### Storage

RAM	512 MB
-----	--------

75740107



IP20

### Materials

RAL colour	RAL 7016 - Anthracite grey
Material	glass
Material family	Glass

### Dimensions

Assembling height	12 mm
-------------------	-------

### Installation, mounting

Installation mode	for flush-mounted and hollow-wall mounting, for vertical and horizontal mounting
-------------------	--

### Connection

Conductor cross-section (flexible), with wire end sleeve	0,75 mm <sup>2</sup>
Conductor cross-section (rigid)	1,5 mm <sup>2</sup>
Connection	Mini-USB 2.0 jack e.g. for external storage media or updates on the upper display edge is accessible without dismantling, 2 USB 2.0 connections on the rear

### Settings

Supported configuration modes	system, easy
-------------------------------	--------------

### Scope of delivery

- Microphone and loudspeaker with echo suppression

### Equipment

Interface type	Ethernet
Text field	no
Light intensity	300 cd/m <sup>2</sup>
Processor	1 GHz
<ul style="list-style-type: none"> <li>- Display illumination can be switched on automatically using brightness sensor</li> <li>- silent, long-lasting convection cooling without fan</li> <li>- card slot with 8 GB SDHC card</li> </ul>	

### Standards

General standards	EN 55022, EN 55024, EN 60950-1
-------------------	--------------------------------

### Software

- Operating system: OS Android 4.1
- Applications (Apps) available in preinstalled Android launcher - without acces to external apps
- Integration of door communication functions in the domovea client or Elcom VideoFON client

### Safety

Protection index IP	IP20
---------------------	------

### Use conditions

Operating temperature	5...45 °C
Storage/transport temperature	-20...60 °C

Identification	
Composition	Control element
Main design line	KNX