



Flush-mounted housing for 7" touch panel KNX, anthracite, lacquered

Technical features

Architecture

Fixing mode flush-mounting

Functions

Touch function no

Controls and indicators

- depending on the software visualisation one and two surface operation, stepless configuration based on sliding and page scrolling by swiping are supported

Connectivity

Connection RJ45 cable in scope of delivery

- with USB/Mini USB type A adapter cable
- with RJ45 connector kit from connector and patch cable

Measurement

Relative humidity (without condensation) 10...90 %

Screen

Display no

Materials

RAL colour RAL 7016 - Anthracite grey

Material Steel

Dimensions

Cavity wall opening (W x H x D) 190 x 126 x 47 mm

Installation, mounting

Installation mode for flush-mounted and hollow-wall mounting, for vertical and horizontal mounting

Scope of delivery

- Microphone and loudspeaker with echo suppression

Equipment

Interface type other

Text field no

- Display illumination can be switched on automatically using brightness sensor
- silent, long-lasting convection cooling without fan

Safety

Protection index IP IP20

- with cleaning cover

75900107

IP20

Use conditions

| | |
|-------------------------------|-------------|
| Storage/transport temperature | -20...60 °C |
|-------------------------------|-------------|

Identification

| | |
|------------------|-------|
| Composition | other |
| Main design line | KNX |
