



## Flush-mounted housing for 10" touch panel KNX, anthracite, lacquered

### Technical features

#### Architecture

Fixing mode flush-mounting

#### Functions

Touch function no

#### Controls and indicators

- depending on the software visualisation one and two surface operation, stepless configuration based on sliding and page scrolling by swiping are supported

#### Connectivity

Connection RJ45 cable in scope of delivery

- with USB/Mini USB type A adapter cable
- with RJ45 connector kit from connector and patch cable

#### Measurement

Relative humidity (without condensation) 10...90 %

#### Screen

Display no

#### Materials

RAL colour RAL 7016 - Anthracite grey

Material Steel

#### Dimensions

Cavity wall opening (W x H x D) 197,7 x 133,6 x 74 mm

#### Installation, mounting

Installation mode for flush-mounted and hollow-wall mounting, for vertical and horizontal mounting

#### Scope of delivery

- Microphone and loudspeaker with echo suppression

#### Equipment

Interface type other

Text field no

- Display illumination can be switched on automatically using brightness sensor
- silent, long-lasting convection cooling without fan

#### Safety

Protection index IP IP20

- with cleaning cover

75900110

IP20

**Use conditions**

---

Storage/transport temperature	-20...60 °C
-------------------------------	-------------

---

**Identification**

---

Composition	other
Main design line	KNX

---