



75261552

IP20

KNX controller comfort 1.1 m KNX - Berker S.1, white glossy

Technical features

Architecture

Fixing mode	flush-mounting
-------------	----------------

Functions

Max. temporisation	306 h
--------------------	-------

Potentiometer for additional delay time	± 50 %
---	--------

Lockout time	8 ms...140 mn
--------------	---------------

- Functions for lighting operating mode: Switching, Value transmitter and Light scene call
- parameter defineable lock function
- with slide switch for OFF/automatic/ON

Compatibility

- also suitable as extension unit

Controls and indicators

Number of switching segments	72
------------------------------	----

Power

Power consumption, KNX	≈ 110 mW
------------------------	----------

Measurement

Detection field, semi-oval shaped	≈ 10 x 12 m
-----------------------------------	-------------

Reach distance

Range, frontal	≈ 10 m
----------------	--------

Range, side	each ≈ 6 m
-------------	------------

Max. transmission range frontally	10 m
-----------------------------------	------

Max. transmission range sideways	6 m
----------------------------------	-----

Cover, door

Cover	with cover to limit detection angle to 90°
-------	--

Detection

Number of detection levels	2
----------------------------	---

Detection angle	180 °
-----------------	-------

Detection angle vertical	0 / 7 °
--------------------------	---------

Detection angle horizontal	0 / 180 °
----------------------------	-----------

Sensor type	detector of movement
-------------	----------------------

Materials

Colour of design line	white
-----------------------	-------

RAL colour	RAL 1013 - Oyster white
------------	-------------------------

Material	thermoplastic
----------	---------------

Surface appearance	glossy
--------------------	--------

Dimensions

Dimensions assembling height	23,5 mm
Nominal mounting height	1,1 m
Optimum mounting height	1,1 m

Lighting control

Response brightness, configurable	3...100 lx / daytime operation
-----------------------------------	--------------------------------

LED control

LED	with red diagnostic LED for brightness-independent walk test function and disassembly message
-----	---

Connection

- for bus coupling unit flush-mounted

Settings

Supported configuration modes	system
Response brightness adjustable by potentiometer	± 50 %
Response sensitivity, settable	20...100 %
Min. temporisation	130 ms
Delay time	≈ 10 s
Additional delay time programmable	130 ms...306 h
- with potentiometers for fine adjustment of the response brightness, sensitivity and delay time	

Equipment

Product type:	product type: movement
- with lighting and message mode	

Safety

Protection index IP	IP20
Halogen free	no
- alarm telegram after disconnection from bus coupling unit, 1-bit	

Use conditions

Operating temperature	-5...45 °C
-----------------------	------------

Identification

Application, usage	KNX - sensors
Product family	product family: physical sensors
Main design line	KNX - Berker S.1
Secondary design line(s)	KNX, Motion detector

Instructions

Information text	Caution: Direct sunlight can lead to false alarms when using alarm application. Avoid using detection field equipment on windows.
------------------	--

Continuous direct sunlight penetrating the upward-pointing detection level can result in failure of the controller. Only suitable for indoor areas!