



80960399



IP20

**Cover for 2gang for push-button module with clear lenses, KNX - Berker S.1/B.3/B.7, polar white, matt, plastic**

Technical features

#### Architecture

Fixing mode flush-mounting

#### Functions

- operating concept "independent push-button" function predefined
- operating concept for "roller shutter/blind" function predefined
- switching of scenes (1..8) possible
- brightness value of the status LED for day/nighttime operation preset, change-over for day/nighttime operation possible
- integrated temperature sensor with output of the measured values
- Colour of status LED uniformly adjustable for complete device
- push-button functions: including switching, dimming, roller shutter/blind, timer, priority, operating mode changeover
- Function for manual interruption of automatic functions already triggered
- operating surfaces as buttons (single-surface operation) and rockers (two-surface operation)
- the brightness of status LEDs are individually adjustable for button/ rocker function
- brightness value of the status LEDs for day/nighttime operation adjustable via object or manually
- value transmitter for dimming, position, brightness temperature values 1 and 2 byte
- integrated temperature sensor with output of the measured values via object
- parameter defineable lock function
- button/rocker functions for switching, dimming, roller shutter/blind, value transmitter 1/2 byte, room thermostat extension unit, priority, scene, automatic control deactivation

#### Controls and indicators

- operating areas configurable as one or two-area operation
- with programming button and red programming LED

#### Voltage

Operating voltage over bus 21...32 V DC

#### Power

Power consumption, KNX ≈ 108 mW

#### Camera

- with 2 clear lenses for the RGB status display of the push-button module

#### Materials

Colour of design line polar white

RAL colour RAL 9010 - Pure white

Material thermoplastic

Surface appearance matt

Type of surface treatment untreated

#### Dimensions

Height 55 mm

#### Connection

- with integral bus coupling unit
- bus connection via connecting terminal

### Settings

Supported configuration modes	system, easy
-------------------------------	--------------

### Equipment

- with integrated buzzer for acoustic identification of the device within the system

### Use

Differentiation characteristic 2 - Sales	with clear lenses
--	-------------------

### Safety

Protection index IP	IP20
---------------------	------

- with dismantling protection

### Use conditions

Operating temperature	-5...45 °C
-----------------------	------------

Storage/transport temperature	-20...70 °C (storage at > 45°C reduces the service life)
-------------------------------	--

- integrated temperature sensor with output of the measured values via object

### Identification

Application, usage	KNX - operating systems
--------------------	-------------------------

Product family	product family: push-button
----------------	-----------------------------

Main design line	KNX - Berker S.1/B.3/B.7
------------------	--------------------------

Secondary design line(s)	KNX, Berker S.1, Berker B.3, Berker B.7
--------------------------	---