



75141150



IP20

Touch sensor 1gang comfort with integral bus coupling unit,	KNX - Berker R.3 - configured, glass polar
white	

Technical features

Λ	ro	h	 ec	tu	ırα

Fixing mode	flush-mounting
Technical version	configured

Functions

- for switch, push-button, dimmer and shutter functions
- Blocking function for sensor surface e.g. for cleaning the glass surface

Compatibility

- extension unit for light scene push-button

Controls and indicators

With LED indication	yes

- operation by gently touching the sensor surfaces on the white LED

Power

Current consumption	12,5 mA
---------------------	---------

Measurement

- value transmitter for dimming, position, brightness and temperature values 1 and 2 byte

Screen

With display	no

Materials

105,105,105	Colour of labelling
glass polar white	Colour of design line
polarwhite	Colour
RAL 9010 - Pure white	RAL colour
glass	Material
glossy	Surface appearance
Tampography	Type of surface treatment

Dimensions

Depth	23 mm
Height	152 mm
Width	81 mm

LED control

LED	with blue operation LED and 2 white status LEDs

Installation, mounting

Installation mode f	or vertica	l mounting
---------------------	------------	------------



Connection

- with integral bus coupling unit
- bus connection via connecting terminal

Scope of delivery

Bus connection included yes

Accessories included

Inscribable, with labelling field

no

- for additional products to complement the installation in matching colours/materials, refer to the Design platform R.1/R.3
- for suitable frames in the same "style" for additional applications, see the Design line R.x

Equipment

Number of actuation points	2
With anti-theft/dismantling protection	yes
Type of configuration	Laserdruck

Use

Differentiation characteristic 3 - Sales

with integral bus coupling unit

Safety

Protection index IP	IP20
Halogen free	no

Use conditions

Operating temperature

-5...45 °C

- temperature measurement via internal temperature sensor or external communication object
- integrated temperature sensor for operation as controller extension unit
- additional connection for external temperature sensor

Identification

Application, usage	KNX - operating systems
Main design line	KNX - Berker R.3 - configured
Secondary design line(s)	KNX, Berker R.3