


75441283



IP20

**KNX object thermostat with integral bus coupling unit, KNX - Berker S.1/B.3/B.7, aluminium matt, lacquered**

Technical features

**Architecture**

Fixing mode flush-mounting

**Functions**

Operating mode operating modes: comfort, standby, night lowering, frost/heat protected, dewpoint

**Controls and indicators**

- with programming button and red programming LED

**Connectivity**

- with 4 independent binary inputs for potential-free contacts e.g. window magnetic contact  
- 4 binary inputs or 2-3 binary inputs and 1-2 outputs parameterisable

**Voltage**

Operating voltage over bus 21...32 V DC

**Electric current**

Bus current consumption (data transfer) max. 7,5 mA

Output current per channel max. 0,8 mA

**Materials**

Colour of design line aluminium

RAL colour RAL 9006 - White aluminium

Material Plastic/metal

Surface appearance matt

Type of surface treatment Painted

**Installation, mounting**

Installation mode without spreader claws

**Connection**

Sensor cable length 50 m

Conductor cross-section (flexible) 0,3...1 mm<sup>2</sup>

Conductor cross-section (rigid) 1,5 mm<sup>2</sup>

- Binary inputs / outputs with screw terminals  
- bus connection via connecting terminal

**Cable**

Cable length, inputs/outputs max. 5 m

**Settings**

Supported configuration modes system

- conduct can be defined for bus voltage return  
- valve protection can be defined

### Equipment

Product type: product type: thermostat

- for heating and/or cooling mode
- heating or cooling possible in 2 stages
- for continuous (PI) or switched (2-point) control
- for single room control

### Use

Differentiation characteristic 3 - Sales with integral bus coupling unit

### Safety

Halogen free no

- with dismantling protection

### Use conditions

Operating temperature -5...45 °C

Energy efficiency class IV (2%)

### Identification

Application, usage KNX - sensors

Product family Product family: heating, ventilation, air conditioning

Main design line KNX - Berker S.1/B.3/B.7

Secondary design line(s) KNX, Berker S.1, Berker B.3, Berker B.7

### Instructions

- Binary input 4 parameter defineable for temperature sensor, order no. 161.