



41431914



SCHUKO socket outlet with screw-in lift terminals, Berker S.1/B.3/B.7, orange matt

Technical features

AICHILECTULE	Arc	hite	cture
--------------	-----	------	-------

Design	according to DIN 49440
Fixing mode	flush-mounting

Connectivity

Type of USB	port	other

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

Electric current

Rated current	16 A

Cover, door

Materials

Surface appearance	matt
Material	thermoplastic
RAL colour	RAL 2003 - Pastel orange
Colour	orange
Colour	orange
Design lines special colours	orange

Dimensions

Insertion depth	32 mm
Installation depth, flush-mounted boxes	31 mm

Installation, mounting

Installation mode	with spreader claws
installation mode	with spreader claws

Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
isla a amazz in life samurin alla	

- with screw-in lift terminals

Use

Differentiation characteristic 3 - Sales	with screw-in lift terminals



Safety

IK protection code against mecanical impacts	05
Protection index IP	IP20
- without enhanced contact protection	
Identification	
Main design line	Berker S.1/B.3/B.7
Secondary design line(s)	Berker S.1, Berker B.3, Berker B.7
Instructions	
Information text	Insert colour-coded.