



85241183



IP20

Blind button Berker S.1/B.3/B.7, aluminium, matt, lacquered

Technical features

Functions

Venetian blind movement time	2 mn
- Memory function for automatic execution of learned up and down times with position	
- Party function, no execution of automatic, radio and extension unit commands (lock-out protection)	

Controls and indicators

- activation of the party function using buttons in up and down direction > 20 sec.

Main electrical features

Nominal voltage	12 V
Frequency	- Hz

Measurement

Relative humidity (without condensation)	0...65 % (without condensation)
--	---------------------------------

Detection

- Not suitable for rain and wind sensors

Materials

Colour of design line	aluminium
Colour	aluminium
Material / workmanship	lacquered
Material	thermoplastic

LED control

LED	LED application module/insert compatibility display, with status LED for memory and party function, red/orange, with indicator LED for lock-out protection
-----	--

Installation, mounting

Installation mode	clamp fastening
-------------------	-----------------

Settings

Lamella adjusting time	(adjustable) 50 ms...2,5 s
Minimum slat adjustment time	≈ 250 ms
Delay time, adjustable	0...500 s
Lamella adjustment on button-press	< 0,4 s

Equipment

Self-retaining for 2 min on button-press	> 0,4 s
Change-over time for change of direction	< 0,6 s

Safety

- with dismantling protection

Use conditions

Operating temperature -5...45 °C

- low intrinsic energy requirement

Identification

Application, usage Blind control

Main design line Berker S.1/B.3/B.7

Secondary design line(s) Electronics platform, Berker S.1, Berker B.3, Berker B.7

Instructions

- Can be switched to orientation led by extension unit.
