



168601



**LED unit 230 V, for switches/push-buttons Light control, black**

Technical features

**Architecture**

Technical version	230 V~, 0.4 mA
-------------------	----------------

**Controls and indicators**

- for change-over/intermediate switch and on/off switch, 2-pole, 10 AX
- for rocker push-buttons and multiple rockers push-buttons, except order no. 503404, 503808

**Main electrical features**

Rated current	0,4 mA
---------------	--------

**Endurance**

Service life of the LED	≈ 100000 h
-------------------------	------------

**Materials**

Colour independent of design lines	black
------------------------------------	-------

**Equipment**

- for lighting and monitoring circuit
- for series switch illuminated

**Identification**

Application, usage	Surface-mounted wet-room installation, Light control
Main design line	Light control
Secondary design line(s)	Light control, ACCESSORIES

**Instructions**

Information text	When several LED units are used, the LED current may result in malfunctioning of the relay/pulse relay. Remedy: Carry along a neutral conductor or connect a capacitor 230 V (1 µF per 10 mA LED current) in parallel with the coil.
<ul style="list-style-type: none"><li>- Refer to the overview for the matching flush-mounted inserts.</li><li>- these marked articles (see symbol) are only suitable for the water-protected flush-mounted installation IP44 in conjunction with the corresponding seal, frame and contact protection box (imprint "IP44").</li></ul>	