



47063515



**SCHUKO socket outlet insert with hinged cover surface-mounted/flush-mounted with enhanced touch protection, Berker W.1, grey matt**

Technical features

**Architecture**

Design	according to DIN 49440
Fixing mode	flush-mounting or surface-mounting

**Connectivity**

Type of USB port	other
------------------	-------

**Main electrical features**

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

**Electric current**

Rated current	16 A
---------------	------

**Cover, door**

Cover	Complete housing
- with hinged cover that falls back, manual clip-in	

**Materials**

Colour of design line	grey
Colour	iron grey
Colour	dark grey
RAL colour	RAL 7011 - Iron grey
Material	thermoplastic
Surface appearance	matt

**Installation, mounting**

Installation mode	for screw fastening
-------------------	---------------------

**Connection**

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with plug-in terminals	

**Use**

Differentiation characteristic 2 - Sales	with enhanced touch protection
--	--------------------------------

### Safety

---

IK protection code against mechanical impacts	05
Protection index IP	IP55
Enhanced contact protection	according to IEC 60884-1
Enhanced contact protection	according to VDE 0620-1:2021-02
- Enhanced contact protection	

---

### Use conditions

---

Operating temperature	-40...30 °C
Storage/transport temperature	-50...50 °C

---

### Identification

---

Application, usage	Surface-mounted wet-room installation
Main design line	Berker W.1

---

### Instructions

---

Information text	Hinged cover springs made of stainless steel, pins of quick-release lock made of ZAMAK
- Inserts will only reach the degree of protection IP55 if mounted with a housing surface mounted or frame for flush-mounted installation.	

---