



75643135



KNX Glass sensor 3gang with thermostat Display, integrated bus coupling unit, KNX - Berker TS Sensor - configured, glass black

Technical features

Architecture

Technical version configured

Functions

With room temperature controller yes

Operating mode controller operating modes: comfort, standby, night and frost/heat protection mode

- with valve protection function
- for switch, push-button, dimmer, blind and thermostat functions

Controls and indicators

With LED indication yes

- operation by gently touching the sensor surfaces on the white LED
- LED display with symbol display
- display of operating mode, controller lockout, room/outside temperature, time (clock required)
- with 2 additional display sensor surfaces

Connectivity

- with button blocking function

Voltage

- operation with non-choked output of KNX voltage supply possible (pay attention to current consumption)
- separate auxiliary power supply needed

Power

Current consumption 23 mA

Measurement

- value transmitter for dimming, position, brightness and temperature values 1 and 2 byte

Screen

With display yes

Materials

Colour of labelling 217,217,217

Colour of design line glass black

Colour black

RAL colour RAL 9005 - Jet black

Material glass

Type of surface treatment Tampography

Material family Glass

Dimensions

Depth	37,7 mm
Depth	5,7 mm
Dimensions (W x H x D)	86 x 160 x 5,7 mm
Height	160 mm
Width	86 mm

LED control

LED	with blue operation LED and 6 white status LEDs
-----	---

Installation, mounting

Installation mode	for vertical mounting
-------------------	-----------------------

Connection

- with integral bus coupling unit
- bus connection via connecting terminal

Settings

- single and two push-button operation parameterisable
- end customer display scope parameterisable

Scope of delivery

Bus connection included	yes
-------------------------	-----

Accessories included

Inscribable, with labelling field	no
-----------------------------------	----

- with adapter ring for dismantling protection and shadow gap formation
- for glass frames in the same "style" for additional applications, see the Design line B.7
- for additional products to complement the installation in matching colours/materials, refer to the Design platform S.1/B.x

Equipment

With anti-theft/dismantling protection	yes
Type of configuration	Laserdruck

- for heating and/or cooling mode with/without auxiliary step
- for individual single room temperature control
- control parameter for heating / cooling unit pre-set
- for continuous (PI) or switched (2-point) control

Use

Differentiation characteristic 2 - Sales	Display
Differentiation characteristic 3 - Sales	integrated bus coupling unit

Safety

Protection index IP	IP20
Halogen free	no

Use conditions

Operating temperature	-5...45 °C
Energy efficiency class	IV (2%)

- additional connection for external temperature sensor
- temperature measurement via internal temperature sensor or external communication object

Identification

Application, usage	KNX - operating systems
Main design line	KNX - Berker TS Sensor - configured
Secondary design line(s)	Berker TS Sensor, KNX

Instructions

Information text	Only suitable for KNX.
------------------	------------------------
