




30863532



Change-over switch insert with rocker surface-mounted/flush-mounted with labelling field - illuminated, Berker W.1, polar white matt

Technical features

Architecture

Fixing mode flush-mounting

Configuration

- Change-over

Main electrical features

Nominal voltage 250 V

Rated voltage 250 V AC

Electric current

Switching current 10 AX

Materials

Colour of design line polar white

Colour white

RAL colour RAL 9010 - Pure white

Material thermoplastic

Surface appearance matt

Dimensions

Depth 42 mm

Labelling field (W x H) 50 x 16 mm

Height 70 mm

Width 70 mm

Installation, mounting

Installation mode for screw fastening

Connection

Type of connection Quickconnect

- Wago clip-in 3-wire connection terminal for wiring
- with N-terminal
- with plug-in terminals

Cable

- with cable entry at top and bottom

Equipment

- for illumination
- with (b blue) 230 V LED unit

Use

Differentiation characteristic 1 - Sales with labelling field - illuminated

Safety

| | |
|---------------------|------|
| Protection index IP | IP55 |
|---------------------|------|

Use conditions

| | |
|-------------------------------|-------------|
| Operating temperature | -40...30 °C |
| Storage/transport temperature | -50...50 °C |

Identification

| | |
|--------------------|---------------------------------------|
| Application, usage | Surface-mounted wet-room installation |
| Main design line | Berker W.1 |

Instructions

| | |
|------------------|--|
| Information text | Pins of quick-release lock made of ZAMAK, For labelling with name, information notice, etc., Labelling field height arranged for P-touch strips 12 mm. |
|------------------|--|

- Inserts will only reach the degree of protection IP55 if mounted with a housing surface mounted or frame for flush-mounted installation.
-