


30863512



**Control change-over switch insert, rocker surface-mounted/flush-mounted with lens, Berker W.1, polar white matt**

Technical features

**Architecture**

Type of control unit	single rocker
Fixing mode	flush-mounting or surface-mounting

**Configuration**

- Change-over

**Main electrical features**

Nominal voltage	250 V
Rated voltage	250 V AC

**Electric current**

Switching current	10 AX
-------------------	-------

**Materials**

Colour of design line	polar white
Colour	white
RAL colour	RAL 9010 - Pure white
Material	thermoplastic
Surface appearance	matt

**Dimensions**

Depth	42 mm
Height	70 mm
Width	70 mm

**Installation, mounting**

Installation mode	for screw fastening
-------------------	---------------------

**Connection**

Type of connection	Quickconnect
<ul style="list-style-type: none"> <li>- with plug-in terminals</li> <li>- with N-terminal</li> </ul>	

**Cable**

- with cable entry at top and bottom

**Equipment**

- with **230 V LED unit**
- for monitoring circuit

**Use**

Differentiation characteristic 2 - Sales	with lens
--	-----------

---

**Safety**

---

Protection index IP	IP55
---------------------	------

---

**Use conditions**

---

Operating temperature	-40...30 °C
Storage/transport temperature	-50...50 °C

---

**Identification**

---

Main design line	Berker W.1
------------------	------------

---

**Instructions**

---

Information text	Pins of quick-release lock made of ZAMAK
------------------	--

---

- Inserts will only reach the degree of protection IP55 if mounted with a housing surface mounted or frame for flush-mounted installation.

---