



50413512



**Push-button insert, NO contact with rocker surface-mounted/flush-mounted with labelling field - illuminated, Berker W.1, polar white matt**

Technical features

#### Architecture

Type of control unit rocker

#### Main electrical features

Nominal voltage 250 V

Rated voltage 250 V AC

#### Electric current

Momentary-contact current 10 A

#### Materials

Colour of design line polar white

Colour polarwhite

Colour white

RAL colour RAL 9010 - Pure white

Material thermoplastic

Surface appearance matt

#### Dimensions

Depth 42 mm

Labelling field (W x H) 50 x 16 mm

Height 71 mm

Width 71 mm

#### Installation, mounting

Installation mode for screw fastening

#### Connection

- Wago clip-in 3-wire connection terminal for wiring
- with N-terminal
- with plug-in terminals

#### Cable

- with cable entry at top and bottom

#### Equipment

- with (b blue) 230 V LED unit

#### Use

Differentiation characteristic 1 - Sales with labelling field - illuminated

#### Safety

Protection index IP IP55

---

**Use conditions**

---

Operating temperature	-40...30 °C
Storage/transport temperature	-50...50 °C

---

**Identification**

---

Application, usage	Surface-mounted wet-room installation
Main design line	Berker W.1

---

**Instructions**

---

Information text	Pins of quick-release lock made of ZAMAK, For labelling with name, information notice, etc., Labelling field height arranged for P-touch strips 12 mm.
------------------	--

---

- Inserts will only reach the degree of protection IP55 if mounted with a housing surface mounted or frame for flush-mounted installation.
-