



30483515

Double change-over switch insert with rocker 2gang surface-mounted/flush-mounted, isolated input terminals Berker W.1

Technical features

Architecture

Type of control unit	double rocker
Fixing mode	flush-mounting
Technical version	isolated input terminals

Configuration

- Change-over contact/change-over switch

Controls and indicators

- No

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC

Electric current

Switching current	10 AX
-------------------	-------

Materials

Colour of design line	grey
Colour	dark grey
RAL colour	RAL 7011 - Iron grey
Material	thermoplastic
Surface appearance	mat

Dimensions

Depth	42 mm
Height	70 mm
Width	70 mm

Installation, mounting

Installation mode	for screw fastening
-------------------	---------------------

Connection

Type of connection	Quickconnect
- with plug-in terminals	

Equipment

- without lighting (cannot be illuminated)

Safety

Protection index IP	IP55
---------------------	------

Use conditions

Operating temperature	-40...30 °C
Storage/transport temperature	-50...50 °C

Identification

Application, usage	Surface-mounted wet-room installation
Main design line	Berker W.1

Instructions

Information text	Pins of quick-release lock made of ZAMAK
------------------	--

- Inserts will only reach the degree of protection IP55 if mounted with a housing surface mounted or frame for flush-mounted installation.
-