



75216001



## KNX binary input 6gang RMD 24 V AC/DC KNX, light grey

### Technical features

#### Architecture

Fixing mode REG

#### Functions

Bus module detachable no

#### Controls and indicators

- with programming button and red programming LED

#### Connectivity

- with 6 independent binary inputs with 2 GND connections

#### Voltage

Input voltage 8...42 V AC

Operating voltage over bus 21...32 V DC

Signal voltage 8...42 V AC/DC

Type of input voltage AC/DC

#### Electric current

Number of entry circuits 6

Signal current 4 mA

#### Materials

Colour independent of design lines light grey

#### Dimensions

Depth 65 mm

Assembling height as from DIN rail 58 mm

Width of rail mounted device (RMD) 2 modules

Height 90 mm

Width 36 mm

#### LED control

LED with 6 yellow status LEDs for input states

#### Connection

Conductor cross-section (flexible) 0,75...2,5 mm<sup>2</sup>

Conductor cross-section (rigid) 0,75...2,5 mm<sup>2</sup>

- with integral bus coupling unit
- with screw terminals
- bus connection via connecting terminal

#### Cable

Input cable length max. 100 m

---

**Settings**

---

Supported configuration modes system

---

**Equipment**

---

Product type: product type: binary input 6gang

---

**Use**

---

Signal duration 200 ms ... 100 % ED

---

**Safety**

---

Protection index IP IP20

---

**Use conditions**

---

Operating temperature -5...45 °C

---

Storage/transport temperature -25...75 °C (storage at > 45°C reduces the service life)

---

**Identification**

---

Application, usage KNX - sensors

---

Product family product family: input

---

Main design line KNX

---