



75216001



## KNX binary input 6gang RMD 24 V AC/DC KNX, light grey

### Technical features

#### Architecture

Fixing mode REG

#### Functions

Bus module detachable no

#### Controls and indicators

- with programming button and red programming LED

#### Connectivity

- with 6 independent binary inputs with 2 GND connections

#### Voltage

Input voltage 8...42 V AC

Operating voltage over bus 21...32 V DC

Signal voltage 8...42 V AC/DC

Type of input voltage AC/DC

#### Electric current

Number of entry circuits 6

Signal current 4 mA

#### Materials

Colour independent of design lines light grey

#### Dimensions

Depth 65 mm

Assembling height as from DIN rail 58 mm

Width of rail mounted device (RMD) 2 modules

Height 90 mm

Width 36 mm

#### LED control

LED with 6 yellow status LEDs for input states

#### Connection

Conductor cross-section (flexible) 0,75...2,5 mm<sup>2</sup>

Conductor cross-section (rigid) 0,75...2,5 mm<sup>2</sup>

- with integral bus coupling unit
- with screw terminals
- bus connection via connecting terminal

#### Cable

Input cable length max. 100 m

### Settings

---

Supported configuration modes	system
-------------------------------	--------

---

### Equipment

---

Product type:	product type: binary input 6gang
---------------	----------------------------------

---

### Use

---

Signal duration	200 ms ... 100 % ED
-----------------	---------------------

---

### Safety

---

Protection index IP	IP20
---------------------	------

---

### Use conditions

---

Operating temperature	-5...45 °C
-----------------------	------------

---

Storage/transport temperature	-25...75 °C (storage at > 45°C reduces the service life)
-------------------------------	----------------------------------------------------------

---

### Identification

---

Application, usage	KNX - sensors
--------------------	---------------

---

Product family	product family: input
----------------	-----------------------

---

Main design line	KNX
------------------	-----

---