



75141835



IP20

KNX Glass sensor 1gang comfort with integral bus coupling unit, KNX - Berker TS Sensor, glass black

Fixing mode	flush-mounting
Functions	
With room temperature controller	yes
 for switch, push-button, dimmer and shutter functions Blocking function for sensor surface e.g. for cleaning the glass surface 	
Compatibility	
- extension unit for light scene push-button	
Controls and indicators	
With LED indication	yes
- operation by gently touching the sensor surfaces on the white LED	
Power	
Current consumption	12,5 mA
Measurement - value transmitter for dimming, position, brightness and temperature value	ues 1 and 2 byte
Screen	
With display	no
Materials	
Colour of design line	glass black
Colour	black
RAL colour	RAL 9005 - Jet black
Material	glass
Surface appearance	glossy
Type of surface treatment	Tampography
Dimensions	
Denth	37 7 mm

Depth	37,7 mm
Depth	5,7 mm
Dimensions (W x H x D)	86 x 160 x 5,7 mm
Height	160 mm
Width	86 mm

LED control

LED

with blue operation LED and 2 white status LEDs

Installation, mounting

Installation mode

for vertical mounting

yes

no

Connection

- with integral bus coupling unit
- bus connection via connecting terminal

Scope of delivery

Bus connection included

Accessories included

Inscribable, with labelling field

- for glass frames in the same "style" for additional applications, see the Design line B.7
- for additional products to complement the installation in matching colours/materials, refer to the Design platform S.1/B.x

Equipment

Number of actuation points	2
With anti-theft/dismantling protection	yes

Use

Differentiation characteristic 3 - Sales

with integral bus coupling unit

-5...45 °C

Use conditions

Operating temperature

- temperature measurement via internal temperature sensor or external communication object

- integrated temperature sensor for operation as controller extension unit

- additional connection for external temperature sensor

Identification

Application, usage	KNX - operating systems
Main design line	KNX - Berker TS Sensor
Secondary design line(s)	KNX, Berker TS Sensor

Instructions

Information text	Only suitable for KNX.
------------------	------------------------