



75142930



IP20

KNX Glass sensor 2gang comfort with integral bus coupling unit, KNX - Berker TS Sensor - configured, glass polar white

Technical features

Architecture

Fixing mode	flush-mounting
Technical version	configured

Functions

With room temperature controller	yes
<ul style="list-style-type: none"> - for switch, push-button, dimmer and shutter functions - Blocking function for sensor surface e.g. for cleaning the glass surface 	

Compatibility

- extension unit for light scene push-button
--

Controls and indicators

With LED indication	yes
- operation by gently touching the sensor surfaces on the white LED	

Power

Current consumption	12,5 mA
---------------------	---------

Measurement

- value transmitter for dimming, position, brightness and temperature values 1 and 2 byte

Screen

With display	no
--------------	----

Materials

Colour of labelling	105,105,105
Colour of design line	glass polar white
Colour	polarwhite
RAL colour	RAL 9010 - Pure white
Material	glass
Surface appearance	glossy/matt
Type of surface treatment	Tampography

Dimensions

Depth	37,7 mm
Depth	5,7 mm
Dimensions (W x H x D)	86 x 160 x 5,7 mm
Height	160 mm
Width	86 mm

LED control

LED	with blue operation LED and 4 white status LEDs
-----	---

Installation, mounting

Installation mode for vertical mounting

Connection

- with integral bus coupling unit
- bus connection via connecting terminal

Scope of delivery

Bus connection included yes

Accessories included

Inscribable, with labelling field no

- for glass frames in the same "style" for additional applications, see the Design line B.7
- for additional products to complement the installation in matching colours/materials, refer to the Design platform S.1/B.x

Equipment

Number of actuation points 4

With anti-theft/dismantling protection yes

Type of configuration Laserdruck

Use

Differentiation characteristic 3 - Sales with integral bus coupling unit

Use conditions

Operating temperature -5...45 °C

- temperature measurement via internal temperature sensor or external communication object
- integrated temperature sensor for operation as controller extension unit
- additional connection for external temperature sensor

Identification

Application, usage KNX - operating systems

Main design line KNX - Berker TS Sensor - configured

Secondary design line(s) KNX, Berker TS Sensor

Instructions

Information text Only suitable for KNX.