



47403512



IP55

## SCHUKO socket outlet with hinged cover surface-mounted Berker W.1, polar white matt

### Technical features

#### Architecture

Design	according to DIN 49440
Fixing mode	surface-mounting

#### Configuration

- ample room for wiring under the bases of the inserts

#### Connectivity

Type of USB port	other
------------------	-------

#### Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

#### Electric current

Rated current	16 A
---------------	------

#### Cover, door

Cover	Complete housing
- with hinged cover that falls back, manual clip-in	

#### Materials

Colour of design line	polar white
Colour	polarwhite
Colour	white
RAL colour	RAL 9010 - Pure white
Material	thermoplastic
Surface appearance	matt

#### Installation, mounting

Installation mode	for screw fastening
-------------------	---------------------

#### Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
<ul style="list-style-type: none"> <li>- with two clip-in places for Wago 2-wire connection terminals in the housing floor</li> <li>- with Wago clip-in 2-wire connection terminal for wiring</li> <li>- with plug-in terminals</li> </ul>	

#### Cable

- with one entry for 2 cables and one entry for cable and tube

#### Equipment

- with full-face sealing on the rear side of housing for cable entry and surface adjustment on the backside

#### Safety

IK protection code against mechanical impacts	05
Protection index IP	IP55
- without enhanced contact protection	

#### Use conditions

Operating temperature	-40...30 °C
Storage/transport temperature	-50...50 °C

#### Identification

Application, usage	Surface-mounted wet-room installation
Main design line	Berker W.1

#### Instructions

Information text	Hinged cover springs made of stainless steel, pins of quick-release lock made of ZAMAK
------------------	--