



47633505



IP55

**SCHUKO socket outlet with hinged cover surface-mounted with enhanced touch protection, Berker W.1, grey/light grey matt**

Technical features

**Architecture**

Design	according to DIN 49440
Fixing mode	surface-mounting

**Configuration**

- ample room for wiring under the bases of the inserts

**Connectivity**

Type of USB port	other
------------------	-------

**Main electrical features**

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

**Electric current**

Rated current	16 A
---------------	------

**Cover, door**

Cover	Complete housing
- with hinged cover that falls back, manual clip-in	

**Materials**

Colour of design line	grey/light grey
Colour	iron grey
Colour	dark grey
RAL colour	RAL 7011 - Iron grey
Material	thermoplastic
Surface appearance	matt

**Installation, mounting**

Installation mode	for screw fastening
-------------------	---------------------

**Connection**

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with two clip-in places for Wago 2-wire connection terminals in the housing floor	
- with Wago clip-in 2-wire connection terminal for wiring	
- with plug-in terminals	

**Cable**

- with one entry for 2 cables and one entry for cable and tube

---

**Equipment**

- with full-face sealing on the rear side of housing for cable entry and surface adjustment on the backside

---

**Use**

Differentiation characteristic 2 - Sales with enhanced touch protection

---

**Safety**

IK protection code against mechanical impacts 05

Protection index IP IP55

Enhanced contact protection according to IEC 60884-1

Enhanced contact protection according to VDE 0620-1:2021-02

- Enhanced contact protection

---

**Use conditions**

Operating temperature -40...30 °C

Storage/transport temperature -50...50 °C

---

**Identification**

Application, usage Surface-mounted wet-room installation

Main design line Berker W.1

---

**Instructions**

Information text Hinged cover springs made of stainless steel, pins of quick-release lock made of ZAMAK

---