



47413515



**SCHUKO socket outlet with hinged cover surface-mounted with labelling field, Berker W.1, grey/light grey matt**

Technical features

**Architecture**

Design	according to DIN 49440
Fixing mode	surface-mounting

**Connectivity**

Type of USB port	other
------------------	-------

**Main electrical features**

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50 Hz
Rated current	16 A

**Cover, door**

- with hinged cover that falls back, manual clip-in

**Materials**

Colour	dark grey
RAL colour	RAL 7011 - Iron grey
Material	thermoplastic
Surface appearance	matt

**Dimensions**

Labelling field (W x H)	50 x 16 mm
Height	76 mm
Width	76 mm

**Connection**

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with plug-in terminals	

**Cable**

- with one entry for 2 cables and one entry for cable and tube

**Equipment**

- with full-face sealing on the rear side of housing for cable entry and surface adjustment on the backside

**Use**

Differentiation characteristic 1 - Sales	with labelling field
--	----------------------

**Safety**

Protection index IP	IP55
- without enhanced contact protection	

---

**Use conditions**

---

Operating temperature	-40...30 °C
Storage/transport temperature	-50...50 °C

---

**Identification**

---

Application, usage	Surface-mounted wet-room installation
Main design line	Berker W.1

---

**Instructions**

---

Information text	Labelling field height arranged for P-touch strips 12 mm., Hinged cover springs made of stainless steel, pins of quick-release lock made of ZAMAK
------------------	---

---