



14093515



FCC socket outlet insert 8pole shielded with hinged cover surface-mounted/flush-mounted, cat.6 with labelling field, Berker W.1, light grey matt

Technical features

Architecture

Design to according to DIN EN 60603-7-5

Connectivity

- with straight outlet
- for RJ11, RJ12 and RJ45 plugs

Voltage

- suitable for PoE+

Frequency

Transmission bandwidth max. 250 MHz

Cover, door

- with transparent hinged cover

Materials

Colour of design line light grey
 Colour code A and B according to TIA/EIA-568-B.2
 Colour light grey
 Material Plastic/metal
 Surface appearance matt
 - Housing made of die-cast zinc

Connection

Cat.6, Class E according to DIN EN 50173-1:2011-09
 Cat.6/class E according to ISO/IEC 11801. 2nd edition
 - with cutting terminals
 - with screen contacting 360° and strain relief

Use

Differentiation characteristic 1 - Sales with labelling field

Safety

Protection index IP IP20
 - with self-closing dust protection cover before jack

Use conditions

Operating temperature -40...30 °C
 Storage/transport temperature -50...50 °C

Identification

Application, usage Communication technology
 Main design line Berker W.1

Instructions

Information text

Hinged cover springs made of stainless steel, pins
of quick-release lock made of ZAMAK