



14093512



**FCC socket outlet insert 8pole shielded with hinged cover surface-mounted/flush-mounted, cat.6 with labelling field, Berker W.1, polar white matt**

Technical features

#### Architecture

Design to according to DIN EN 60603-7-5

#### Connectivity

- with straight outlet
- for RJ11, RJ12 and RJ45 plugs

#### Voltage

- suitable for PoE+

#### Frequency

Transmission bandwidth max. 250 MHz

#### Cover, door

- with transparent hinged cover

#### Materials

Colour of design line polar white  
 Colour code A and B according to TIA/EIA-568-B.2  
 Colour polarwhite  
 Material Plastic/metal  
 Surface appearance matt  
 - Housing made of die-cast zinc

#### Connection

Cat.6, Class E according to DIN EN 50173-1:2011-09  
 Cat.6/class E according to ISO/IEC 11801. 2nd edition  
 - with cutting terminals  
 - with screen contacting 360° and strain relief

#### Use

Differentiation characteristic 1 - Sales with labelling field

#### Safety

Protection index IP IP20  
 - with self-closing dust protection cover before jack

#### Use conditions

Operating temperature -40...30 °C  
 Storage/transport temperature -50...50 °C

#### Identification

Application, usage Communication technology  
 Main design line Berker W.1

**Instructions**

Information text

Hinged cover springs made of stainless steel, pins  
of quick-release lock made of ZAMAK