product sheet 30763522





30763522



IP55

| Technical features | |
|---|-------------------|
| Architecture | |
| Fixing mode | surface-mount |
| Configuration | |
| ample room for wiring under the bases of the inserts Change-over | |
| Main electrical features | |
| Nominal voltage | 25 |
| Rated voltage | 250 V |
| Electric current | |
| Switching current | 10 |
| Materials | |
| Colour of design line | polar w |
| Colour | wh |
| RAL colour | RAL 9010 - Pure w |
| Material | thermopla |
| Surface appearance | n |
| Dimensions | |
| Depth | 61,5 r |
| Height | 76 r |
| Width | 76 r |
| Installation, mounting | |
| Installation mode | for screw fasten |
| Connection | |
| Type of connection | Quickconn |
| with two clip-in places for Wago 2-wire connection terminals in the housing floor with Wago clip-in 2-wire connection terminal for wiring with N-terminal with plug-in terminals | |
| Cable | |
| - with one entry for 2 cables and one entry for cable and tube | |

- with {\b blue} 230 V LED unit
- for illumination
 with full-face sealing on the rear side of housing for cable entry and surface adjustment on the backside

Use

Differentiation characteristic 2 - Sales

with lens



Safety

| Protection index IP | IP58 |
|-------------------------------|--|
| Use conditions | |
| Operating temperature | -4030 °C |
| Storage/transport temperature | -5050 °C |
| Identification | |
| Main design line | Berker W.1 |
| Instructions | |
| Information text | Pins of quick-release lock made of ZAMAK |