





**IP55** 

### Control change-over switch surface-mounted with lens, Berker W.1, polar white matt

Technical features

#### Architecture

Fixing mode surface-mounting

### Configuration

- Change-over

#### Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC

#### Electric current

Switching current 10 AX

#### Materials

Colour of design line	polar white
Colour	white
RAL colour	RAL 9010 - Pure white
Material	thermoplastic
Surface appearance	matt

#### **Dimensions**

Depth	61,5 mm
Height	76 mm
Width	76 mm

### Installation, mounting

Installation mode for screw fastening

### Connection

Type of connection Quickconnect

- with two clip-in places for Wago 2-wire connection terminals in the housing floor
- with Wago clip-in 2-wire connection terminal for wiring
- with plug-in terminals
- with N-terminal

# Cable

- with one entry for 2 cables and one entry for cable and tube

### Equipment

- with {\b red} 230 V LED unit
- for monitoring circuit
- with full-face sealing on the rear side of housing for cable entry and surface adjustment on the backside

## Use

Differentiation characteristic 2 - Sales

with lens



Safety	
Protection index IP	IP55
Use conditions	
Operating temperature	-4030 °C
Storage/transport temperature	-5050 °C
Identification	
Main design line	Berker W.1
Instructions	
Information text	Pins of quick-release lock made of ZAMAK