



50453522



**IP55**

**Push-button, NO contact surface-mounted Berker W.1, polar white matt**

Technical features

**Architecture**

Type of control unit single rocker

**Configuration**

- ample room for wiring under the bases of the inserts

**Main electrical features**

Nominal voltage 250 V

Rated voltage 250 V AC

**Electric current**

Momentary-contact current 10 A

**Materials**

Colour of design line polar white

Colour polarwhite

Colour white

RAL colour RAL 9010 - Pure white

Material Plastic/metal

Surface appearance matt

**Installation, mounting**

Installation mode for screw fastening

**Connection**

- with Wago clip-in 2-wire connection terminal for wiring
- with two clip-in places for Wago 2-wire connection terminals in the housing floor
- with plug-in terminals

**Cable**

- with one entry for 2 cables and one entry for cable and tube

**Equipment**

- with full-face sealing on the rear side of housing for cable entry and surface adjustment on the backside

**Safety**

Protection index IP IP55

**Use conditions**

Operating temperature -40...30 °C

Storage/transport temperature -50...50 °C

**Identification**

Main design line Berker W.1

**Instructions**

---

Information text

Pins of quick-release lock made of ZAMAK

- Inserts will only reach the degree of protection IP55 if mounted with a housing surface mounted or frame for flush-mounted installation.
-