



30723505



IP55

## On/off switch 2pole with imprint "0" and "I" surface-mounted Berker W.1, grey/light grey matt

### Technical features

#### Architecture

Type of control unit	single rocker
Fixing mode	surface-mounting

#### Configuration

- ample room for wiring under the bases of the inserts
- 2 x 1-pole Off

#### Connectivity

- with mechanical encoding of rocker mount, that allows only one correct positioning of the rocker on the insert

#### Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC

#### Electric current

Switching current	10 AX
-------------------	-------

#### Materials

Colour of design line	grey/light grey
Colour	dark grey
RAL colour	RAL 7011 - Iron grey
Material	thermoplastic
Surface appearance	matt

#### Dimensions

Depth	61,5 mm
Height	76 mm
Width	76 mm

#### Installation, mounting

Installation mode	for screw fastening
-------------------	---------------------

#### Connection

Type of connection	Quickconnect
--------------------	--------------

- with Wago clip-in 2-wire connection terminal for wiring
- with two clip-in places for Wago 2-wire connection terminals in the housing floor
- with N-terminal
- with plug-in terminals

#### Cable

- with one entry for 2 cables and one entry for cable and tube

#### Equipment

- with full-face sealing on the rear side of housing for cable entry and surface adjustment on the backside

---

**Safety**

---

Protection index IP	IP55
---------------------	------

---

**Use conditions**

---

Operating temperature	-40...30 °C
Storage/transport temperature	-50...50 °C

---

**Identification**

---

Application, usage	Surface-mounted wet-room installation
Main design line	Berker W.1

---

**Instructions**

---

Information text	Pins of quick-release lock made of ZAMAK
------------------	--

---