



30753505



IP55

**Series switch surface-mounted Berker W.1, grey/light grey matt**

Technical features

**Architecture**

Type of control unit	double rocker
Fixing mode	surface-mounting

**Configuration**

- ample room for wiring under the bases of the inserts
- series

**Main electrical features**

Nominal voltage	250 V
Rated voltage	250 V AC

**Electric current**

Switching current	10 AX
-------------------	-------

**Materials**

Colour of design line	grey/light grey
Colour	dark grey
RAL colour	RAL 7011 - Iron grey
Material	thermoplastic
Surface appearance	matt

**Dimensions**

Depth	61,5 mm
Height	76 mm
Width	76 mm

**Installation, mounting**

Installation mode	for screw fastening
-------------------	---------------------

**Connection**

Type of connection	Quickconnect
<ul style="list-style-type: none"> <li>- with Wago clip-in 2-wire connection terminal for wiring</li> <li>- with two clip-in places for Wago 2-wire connection terminals in the housing floor</li> <li>- with plug-in terminals</li> </ul>	

**Cable**

- with one entry for 2 cables and one entry for cable and tube

**Equipment**

- with full-face sealing on the rear side of housing for cable entry and surface adjustment on the backside

**Safety**

Protection index IP	IP55
---------------------	------

---

**Use conditions**

---

Operating temperature	-40...30 °C
Storage/transport temperature	-50...50 °C

---

**Identification**

---

Application, usage	Surface-mounted wet-room installation
Main design line	Berker W.1

---

**Instructions**

---

Information text	Pins of quick-release lock made of ZAMAK
------------------	--

---