



30753502



IP55

Series switch surface-mounted Berker W.1, polar white matt

Technical features

Architecture

Type of control unit	double rocker
Fixing mode	surface-mounting

Configuration

- ample room for wiring under the bases of the inserts
- series

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC

Electric current

Switching current	10 AX
-------------------	-------

Materials

Colour of design line	polar white
Colour	white
RAL colour	RAL 9010 - Pure white
Material	thermoplastic
Surface appearance	matt

Dimensions

Depth	61,5 mm
Height	76 mm
Width	76 mm

Installation, mounting

Installation mode	for screw fastening
-------------------	---------------------

Connection

Type of connection	Quickconnect
<ul style="list-style-type: none">- with Wago clip-in 2-wire connection terminal for wiring- with two clip-in places for Wago 2-wire connection terminals in the housing floor- with plug-in terminals	

Cable

- with one entry for 2 cables and one entry for cable and tube

Equipment

- with full-face sealing on the rear side of housing for cable entry and surface adjustment on the backside

Safety

Protection index IP	IP55
---------------------	------

Use conditions

Operating temperature	-40...30 °C
Storage/transport temperature	-50...50 °C

Identification

Application, usage	Surface-mounted wet-room installation
Main design line	Berker W.1

Instructions

Information text	Pins of quick-release lock made of ZAMAK
------------------	--