



32713505



IP55

**Key change-over switch with imprint surface-mounted, isolated input terminals Lock - identical lockings, Key can be removed in 2 positions, Berker W.1, grey/light grey matt**

Technical features

### Architecture

Type of control unit Key

### Main electrical features

Nominal voltage 240 V

Rated voltage 240 V AC

### Electric current

Switching current 10 A

### Materials

Colour of design line grey/light grey

Colour iron grey

Colour dark grey

RAL colour RAL 7011 - Iron grey

Material thermoplastic

Surface appearance matt

### Dimensions

Depth 64 mm

Height 76 mm

Width 76 mm

### Installation, mounting

Installation mode for screw fastening

### Connection

- with two clip-in places for Wago 2-wire connection terminals in the housing floor
- with Wago clip-in 2-wire connection terminal for wiring
- with screw terminals

### Cable

- with one entry for 2 cables and one entry for cable and tube

### Equipment

- with full-face sealing on the rear side of housing for cable entry and surface adjustment on the backside
- for master-key systems

### Use

Differentiation characteristic 2 - Sales Lock - identical lockings

Differentiation characteristic 3 - Sales Key can be removed in 2 positions

### Safety

Protection index IP IP55

- with 2 keys

---

**Use conditions**

---

Operating temperature	-40...30 °C
Storage/transport temperature	-50...50 °C

---

**Identification**

---

Main design line	Berker W.1
------------------	------------

---

**Instructions**

---

Information text	Pins of quick-release lock made of ZAMAK
------------------	--

---