



47803515



IP55

**Combination change-over switch/SCHUKO socket outlet with hinged cover surface-mounted Berker W.1, grey/light grey matt**

Technical features

**Configuration**

- ample room for wiring under the bases of the inserts

**Main electrical features**

|                 |          |
|-----------------|----------|
| Nominal voltage | 250 V    |
| Rated voltage   | 250 V AC |
| Rated current   | 16 A     |

**Electric current**

|                   |       |
|-------------------|-------|
| Switching current | 10 AX |
|-------------------|-------|

**Cover, door**

|   |                  |
|---|------------------|
| Cover   | Complete housing |
| - with hinged cover that falls back, manual clip-in |                  |

**Materials**

|                       |                      |
|-----------------------|----------------------|
| Colour of design line | grey/light grey      |
| Colour                | iron grey            |
| Colour                | dark grey            |
| RAL colour            | RAL 7011 - Iron grey |
| Material              | thermoplastic        |
| Surface appearance    | matt                 |

**Dimensions**

|                 |        |
|-----------------|--------|
| Contact spacing | > 3 mm |
|-----------------|--------|

**Installation, mounting**

|                   |                       |
|-------------------|-----------------------|
| Installation mode | for vertical mounting |
|-------------------|-----------------------|

**Connection**

- with plug-in terminals

**Cable**

- with one entry for 2 cables and one entry for cable and tube

**Equipment**

- with full-face sealing on the rear side of housing for cable entry and surface adjustment on the backside
- change-over switch and socket outlet connectable separately

**Safety**

|                                       |      |
|---------------------------------------|------|
| Protection index IP                   | IP55 |
| - without enhanced contact protection |      |

---

**Use conditions**

---

|                               |             |
|-------------------------------|-------------|
| Operating temperature         | -40...30 °C |
| Storage/transport temperature | -50...50 °C |

---

**Identification**

---

|                    |                                       |
|--------------------|---------------------------------------|
| Application, usage | Surface-mounted wet-room installation |
| Main design line   | Berker W.1                            |

---

**Instructions**

---

|                  |  |
|------------------|--|
| Information text | Hinged cover springs made of stainless steel, pins of quick-release lock made of ZAMAK |
|------------------|--|

---