



30753522



IP55

Blind series switch 1pole with imprinted symbol arrow surface-mounted Berker W.1, polar white matt

Technical features

Architecture

| | |
|----------------------|------------------|
| Type of control unit | double rocker |
| Fixing mode | surface-mounting |

Configuration

- with mechanical and electrical interlock to prevent mutual switch-on

Main electrical features

| | |
|-----------------|----------|
| Nominal voltage | 250 V |
| Rated voltage | 250 V AC |

Electric current

| | |
|-------------------|------|
| Switching current | 10 A |
|-------------------|------|

Materials

| | |
|-----------------------|-----------------------|
| Colour of design line | polar white |
| Colour | polarwhite |
| Colour | white |
| RAL colour | RAL 9010 - Pure white |
| Material | thermoplastic |
| Surface appearance | matt |

Dimensions

| | |
|--------|-------|
| Depth | 62 mm |
| Height | 76 mm |
| Width | 76 mm |

Installation, mounting

| | |
|-------------------|---------------------|
| Installation mode | for screw fastening |
|-------------------|---------------------|

Connection

- with two clip-in places for Wago 2-wire connection terminals in the housing floor
- with Wago clip-in 2-wire connection terminal for wiring
- with plug-in terminals

Cable

- with one entry for 2 cables and one entry for cable and tube

Equipment

- with full-face sealing on the rear side of housing for cable entry and surface adjustment on the backside

Safety

| | |
|---------------------|------|
| Protection index IP | IP55 |
|---------------------|------|

Use conditions

| | |
|-------------------------------|-------------|
| Operating temperature | -40...30 °C |
| Storage/transport temperature | -50...50 °C |

Identification

| | |
|--------------------|---------------------------------------|
| Application, usage | Surface-mounted wet-room installation |
| Main design line | Berker W.1 |

Instructions

| | |
|------------------|--|
| Information text | Pins of quick-release lock made of ZAMAK |
|------------------|--|