




35623505



IP55

**Control on/off switch 2pole with imprint "Heizung - 0 - I" surface-mounted with lens, Berker W.1, grey/light grey matt**

#### Technical features

#### Architecture

Fixing mode	surface-mounting
-------------	------------------

#### Connectivity

- with mechanical encoding of rocker mount, that allows only one correct positioning of the rocker on the insert

#### Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC

#### Electric current

Switching current	10 A
-------------------	------

#### Materials

Colour of design line	grey/light grey
Colour	dark grey
RAL colour	RAL 7011 - Iron grey
Material	thermoplastic
Surface appearance	matt

#### Dimensions

Depth	62 mm
Height	76 mm
Width	76 mm

#### Installation, mounting

Installation mode	for screw fastening
-------------------	---------------------

#### Connection

Type of connection	Quickconnect
--------------------	--------------

- with two clip-in places for Wago 2-wire connection terminals in the housing floor
- with Wago clip-in 2-wire connection terminal for wiring
- with plug-in terminals

#### Cable

- with one entry for 2 cables and one entry for cable and tube

#### Equipment

- with 230 V LED unit
- for monitoring circuit
- with full-face sealing on the rear side of housing for cable entry and surface adjustment on the backside
- Not suitable for heating systems > 50 kW.

<b>Use</b>	
Differentiation characteristic 2 - Sales	with lens
<b>Safety</b>	
Protection index IP	IP55
<b>Use conditions</b>	
Operating temperature	-40...30 °C
Storage/transport temperature	-50...50 °C
<b>Identification</b>	
Application, usage	Surface-mounted wet-room installation
Main design line	Berker W.1
<b>Instructions</b>	
Information text	Pins of quick-release lock made of ZAMAK