



41452089



SCHUKO socket outlet Installation position variable in 45° steps, with screw-in lift terminals, Serie R.classic, polar white glossy

Technical features

Architecture

| | |
|-------------|------------------------|
| Design | according to DIN 49440 |
| Fixing mode | flush-mounting |

Connectivity

| | |
|------------------|-------|
| Type of USB port | other |
|------------------|-------|

Main electrical features

| | |
|-----------------|----------|
| Nominal voltage | 250 V |
| Rated voltage | 250 V AC |
| Frequency | 50/60 Hz |
| Rated current | 16 A |

Electric current

| | |
|---------------|------|
| Rated current | 16 A |
|---------------|------|

Cover, door

| | |
|-------|---------------------|
| Cover | Central cover plate |
|-------|---------------------|

Materials

| | |
|-----------------------|-----------------------|
| Colour of labelling | 105,105,105 |
| Colour of design line | polar white |
| Colour | polarwhite |
| Colour | white |
| RAL colour | RAL 9010 - Pure white |
| Material | thermoplastic |
| Material for printing | ASA polar white |
| Surface appearance | glossy |

Dimensions

| | |
|---|-------|
| Insertion depth | 32 mm |
| Installation depth, flush-mounted boxes | 31 mm |

Installation, mounting

| | |
|-------------------|---------------------|
| Installation mode | with spreader claws |
|-------------------|---------------------|

Connection

| | |
|----------------------|---------------------------------|
| Connection terminals | according to IEC 60884-1 |
| Connection terminals | according to VDE 0620-1:2021-02 |
| - | with screw-in lift terminals |

Equipment

| | |
|-----------------------|------------|
| Type of configuration | Laserdruck |
|-----------------------|------------|

Use

| | |
|--|---|
| Differentiation characteristic 2 - Sales | Installation position variable in 45° steps |
| Differentiation characteristic 3 - Sales | with screw-in lift terminals |

Safety

| | |
|---|------|
| IK protection code against mechanical impacts | 05 |
| Protection index IP | IP20 |
| - without enhanced contact protection | |

Identification

| | |
|------------------|-----------------|
| Main design line | Serie R.classic |
|------------------|-----------------|
