



75164593

IP20

**B.IQ push-button 4gang comfort KNX - Berker B.IQ, Stainless steel, metal brushed**

Technical features

**Architecture**

|                   |                |
|-------------------|----------------|
| Fixing mode       | flush-mounting |
| Technical version | 4gang          |

**Functions**

|   |    |
|---|----|
| With room temperature controller                        | no |
| - for switch, push-button, dimmer and shutter functions |    |

**Compatibility**

- extension unit for light scene push-button

**Controls and indicators**

|  |     |
|--|-----|
| With LED indication  | yes |
| Number of buttons  | 4   |
| - second operating level via object or 3-button handle                   |     |
| - lockable via 3-button actuation  |     |
| - one push-button operation for switching, pushing, shutters and dimming |     |

**Measurement**

- value transmitter for dimming, position, brightness and temperature values 1 and 2 byte

**Screen**

|              |    |
|--------------|----|
| With display | no |
|--------------|----|

**Materials**

|                           |                             |
|---------------------------|-----------------------------|
| Colour of design line     | Stainless steel             |
| Colour                    | Stainless steel             |
| RAL colour                | RAL 9022 - Pearl light grey |
| Material / workmanship    | metal brushed               |
| Material                  | stainless steel             |
| Surface appearance        | matt                        |
| Type of surface treatment | brushed                     |

**Dimensions**

|                   |          |
|-------------------|----------|
| Assembling height | 16,7 mm  |
| Height            | 118,1 mm |
| Width             | 88,5 mm  |

**LED control**

|     |  |
|-----|--|
| LED | with blue operation LED and 8 white status LEDs (labelling field illumination) |
|-----|--|

**Connection**

- for bus coupling unit flush-mounted

### Settings

|  |            |
|--|------------|
| Supported configuration modes                          | system, PB |
| - single and two push-button operation parameterisable |            |

### Scope of delivery

|                         |    |
|-------------------------|----|
| Bus connection included | no |
|-------------------------|----|

### Accessories included

|  |    |
|--|----|
| Inscribable, with labelling field  | no |
| - for installation in single standard wall boxes   |    |
| - for stainless steel frames in the same "style" for additional applications, see the Design line B.7                        |    |
| - for additional products to complement the installation in matching colours/materials, refer to the Design platform S.1/B.x |    |

### Equipment

|  |                    |
|--|--------------------|
| Number of actuation points             | 8                  |
| With anti-theft/dismantling protection | yes                |
| Product type:                          | product type: B.IQ |

### Safety

|   |      |
|---|------|
| Protection index IP   | IP20 |
| Halogen free  | no   |
| - with dismantling protection   |      |
| - alarm telegram after disconnection from bus coupling unit 1 bit or 1 byte |      |

### Use conditions

|                       |            |
|-----------------------|------------|
| Operating temperature | -5...45 °C |
|-----------------------|------------|

### Identification

|                          |                             |
|--------------------------|-----------------------------|
| Application, usage       | KNX - operating systems     |
| Product family           | product family: push-button |
| Main design line         | KNX - Berker B.IQ           |
| Secondary design line(s) | KNX, Berker B.IQ            |