

75162590

IP20

B.IQ push-button 2gang comfort KNX - Berker B.IQ, glass polar white

Technical features

Architecture	
Fixing mode	flush-mounting
Technical version	2gang
Functions	
With room temperature controller	na
- for switch, push-button, dimmer and shutter functions	
Compatibility	
 extension unit for light scene push-button 	
Controls and indicators	
With LED indication	yes
Number of buttons	2
 activation of second user level via object one push-button operation for switching, pushing, shutters and dimming 	
Measurement	
- value transmitter for dimming, position, brightness and temperature values 1	and 2 byte
Screen	
With display	no
Materials	
Colour of design line	glass polar white
Colour	polarwhite

Colour of design line	glass polar white
Colour	polarwhite
RAL colour	RAL 9010 - Pure white
Material	glass
Surface appearance	glossy
Type of surface treatment	Painted

Dimensions

Assembling height	16,7 mm
Height	88,5 mm
Width	88,5 mm

LED control

LED	with blue operation LED and 4 white status LEDs
	(labelling field illumination)

Connection

- for bus coupling unit flush-mounted



Settings

Supported configuration modes	system, PE
- single and two push-button operation parameterisable	
Scope of delivery	
Bus connection included	no
Accessories included	
Inscribable, with labelling field	nd
 for installation in single standard wall boxes for glass frames in the same "style" for additional application for additional products to complement the installation in ma platform S.1/B.x 	
Equipment	
Number of actuation points	
With anti-theft/dismantling protection	yes
Product type:	product type: B.IC
Safety	
Protection index IP	IP20
Halogen free	n
 with dismantling protection alarm telegram after disconnection from bus coupling unit 1 	bit or 1 byte
Use conditions	
Operating temperature	-545 °C
Identification	
	KNX - operating systems
Application, usage	
Application, usage Product family	product family: push-buttor
	product family: push-buttor KNX - Berker B.IC