

75161099

IP20

Technical version 1g Functions With room temperature controller - for switch, push-button, dimmer and shutter functions Compatibility - extension unit for light scene push-button Controls and indicators With LED indication Number of buttons Measurement - dimming / position value transmitter 1 byte Screen With display Materials Colour of labelling 105,105, Colour of labelling 105,105, Colour of design line Colour of polarw RAL colour RAL 9010-Pure w Material therroopta Surface appearance r Type of surface treatment Dimensions LED control LED with blue operation LED and 2 white status L (labelling field illuminat Connection	Architecture	
Functions With room temperature controller - for switch, push-button, dimmer and shutter functions Compatibility - extension unit for light scene push-button Controls and indicators With LED indication Number of buttons Measurement - dimming / position value transmitter 1 byte Screen With display Materials Colour of labelling 105,105, Colour of design line polar w Colour RAL 9010 - Pure w Material thermopla Surface appearance r Type of surface treatment untreation Dimensions 48,51 LED with blue operation LED and 2 white status L (labelling field illuminat Connection (labelling field illuminat	Fixing mode	flush-moun
With room temperature controller - for switch, push-button, dimmer and shutter functions Compatibility - extension unit for light scene push-button Controls and indicators With LED indication Number of buttons Measurement - dimming / position value transmitter 1 byte Screen With display Materials Colour of labelling 105,105, Colour of labelling 105,105, Colour of labelling 105,105, Colour of labelling 105,105, Colour of sign line polarw Colour of superance n Type of surface treatment untread Dimensions 16,77 Height 88,51 LED with blue operation LED and 2 white status LI (labelling field illuminat Connection (labelling field illuminat	Technical version	1g
for switch, push-button, dimmer and shutter functions Compatibility extension unit for light scene push-button Controls and indicators With LED indication Number of buttons Measurement dimming / position value transmitter 1 byte Screen With display Materials Colour of labelling 105,105, Colour of labelling 105,105, Colour of design line polarw Colour polarw Colour polarw Colour Palaelling 105,105, Colour of design line colour polarw Colour polarw Colour BAL 9010 - Pure w Material thermopla Surface appearance r Type of surface treatment untree Dimensions LED with blue operation LED and 2 white status LI (labelling field illuminat Connection field surface line line line line line line line lin	Functions	
Compatibility - extension unit for light scene push-button Controls and indicators With LED indication Number of buttons Measurement - dimming / position value transmitter 1 byte Screen With display Materials Colour of labelling 105,105, Colour of labelling 105,105, Colour of labelling 105,105, Colour of design line colour polarw RAL colour RAL colour RAL option Pure w Material thermopla Surface appearance r Type of surface treatment Dimensions LED with blue operation LED and 2 white status LI (labelling field illuminat Connection - for bus coupling unit flush-mounted	With room temperature controller	
extension unit for light scene push-button Controls and indicators With LED indication Number of buttons Measurement dimming / position value transmitter 1 byte Screen With display Materials Colour of labelling 105,105, Colour of l	- for switch, push-button, dimmer and shutter fund	ctions
Controls and indicators With LED indication Number of buttons Measurement - dimming / position value transmitter 1 byte Screen With display Materials Colour of labelling 105,105, Colour of design line polar w Colour of design line polar w Colour material Surface appearance n Type of surface treatment untreat Dimensions 16,7 Height 88,5 LED control (abelling field illuminat Connection (abelling field illuminat - for bus coupling unit flush-mounted -	Compatibility	
With LED indication Number of buttons Measurement - dimming / position value transmitter 1 byte Screen With display Materials Colour of labelling Colour of labelling Colour of labelling Diar W Diar W Dimensions Assembling height LED with blue operation LED and 2 white status LE (labelling field illuminat Connection	- extension unit for light scene push-button	
Number of buttons Measurement - dimming / position value transmitter 1 byte Screen With display Materials Colour of labelling 105,105, Colour of design line polar w Colour	Controls and indicators	
Measurement - dimming / position value transmitter 1 byte Screen With display Materials Colour of labelling 105,105, Colour of design line polar w Colour of design line polar w Colour polar w RAL colour RAL 9010 - Pure w Material thermopla Surface appearance r Type of surface treatment untreat Dimensions 16,7 Height 88,5 LED with blue operation LED and 2 white status L (labelling field illuminat Connection - - for bus coupling unit flush-mounted -	With LED indication	
- dimming / position value transmitter 1 byte Screen With display Materials Colour of labelling Colour of design line Colour Connection Connection Colour Co	Number of buttons	
Screen With display Materials Colour of labelling Colour of design line Colour Colour RAL colour RAL 9010 - Pure w Material Control LED With blue operation LED and 2 white status L (labelling field illuminat Connection - for bus coupling unit flush-mounted	Measurement	
With display Materials Colour of labelling 105,105, Colour of design line polar w Colour polar w Colour polar w RAL colour RAL 9010 - Pure w Material thermopla Surface appearance r Type of surface treatment untreative Dimensions 16,7 Height 88,5 Width 88,5 LED control LED LED with blue operation LED and 2 white status LI (labelling field illuminat Connection - - for bus coupling unit flush-mounted -	- dimming / position value transmitter 1 byte	
Materials Colour of labelling 105,105, Colour of design line polar w Colour polar w Colour polar w RAL colour RAL 9010 - Pure w Material thermopla Surface appearance r Type of surface treatment untreating Dimensions 16,7 Height 88,5 Width 88,5 LED control LED LED with blue operation LED and 2 white status LI (labelling field illumination of the status LI (labelling field illumination of t	Screen	
Colour of labelling 105,105, Colour of design line polar w Colour Of design line polar w RAL colour RAL 9010 - Pure w Material thermopla Surface appearance r Type of surface treatment untrea Dimensions Assembling height 16,7 Height 88,5 Width 88,5 LED control LED with blue operation LED and 2 white status L (labelling field illuminat Connection - for bus coupling unit flush-mounted	With display	
Colour of labelling 105,105, Colour of design line polar w Colour Of design line polar w RAL colour RAL 9010 - Pure w Material thermopla Surface appearance r Type of surface treatment untrea Dimensions Assembling height 16,7 Height 88,5 Width 88,5 LED control LED with blue operation LED and 2 white status L (labelling field illuminat Connection - for bus coupling unit flush-mounted	Materiala	
Colour of design line polar w Colour polarw RAL colour RAL 9010 - Pure w Material thermopla Surface appearance n Type of surface treatment untreat Dimensions 16,7 Height 88,5 Width 88,5 LED control LED LED with blue operation LED and 2 white status Ling field illuminat Connection - - for bus coupling unit flush-mounted -		105.105.
Colour polarw RAL colour RAL 9010 - Pure w Material thermopla Surface appearance r Type of surface treatment untreating Dimensions 16,7 Height 88,5 Width 88,5 LED control (labelling field illuminat Connection - for bus coupling unit flush-mounted		
Material thermopla Surface appearance r Type of surface treatment untree Dimensions Assembling height 16,7 Height 88,5 Width 88,5 LED control LED with blue operation LED and 2 white status L (labelling field illuminat Connection - for bus coupling unit flush-mounted		polarw
Surface appearance r Type of surface treatment untrea Dimensions Assembling height 16,7 Height 88,5 Width 88,5 LED control LED with blue operation LED and 2 white status L (labelling field illuminat Connection - for bus coupling unit flush-mounted	RAL colour	RAL 9010 - Pure w
Type of surface treatment untreal Dimensions Assembling height 16,7 Height 88,5 Width 88,5 LED control LED with blue operation LED and 2 white status LI (labelling field illuminat Connection - for bus coupling unit flush-mounted	Material	thermopla
Dimensions 16,7 Assembling height 16,7 Height 88,5 Width 88,5 LED control 1000000000000000000000000000000000000	Surface appearance	n
Assembling height 16,7 Height 88,5 Width 88,5 LED control LED with blue operation LED and 2 white status Li (labelling field illuminat Connection - for bus coupling unit flush-mounted	Type of surface treatment	untrea
Height 88,5 1 Width 88,5 1 LED control LED with blue operation LED and 2 white status Li (labelling field illuminat Connection - for bus coupling unit flush-mounted	Dimensions	
Width 88,5 LED control LED with blue operation LED and 2 white status Li (labelling field illuminat Connection - for bus coupling unit flush-mounted	Assembling height	16,7 ו
LED control LED with blue operation LED and 2 white status L (labelling field illuminat Connection - for bus coupling unit flush-mounted	Height	88,5 ו
LED with blue operation LED and 2 white status L (labelling field illuminat Connection - for bus coupling unit flush-mounted	Width	88,5 1
(labelling field illuminat Connection - for bus coupling unit flush-mounted	LED control	
- for bus coupling unit flush-mounted	LED	with blue operation LED and 2 white status Lf (labelling field illuminati
	Connection	
Scope of delivery	 for bus coupling unit flush-mounted 	
SCORE OF DEWERY	Coons of delivery	
	Bus connection included	

B.IQ push-button 1gang KNX - Berker B.IQ, polar white matt

Inscribable, with labelling field	t
 for installation in single standard wall boxes for plastic frames in the same "style" for additional applications, s for additional products to complement the installation in matching platform S.1/B.x 	
Equipment	
Number of actuation points	
With anti-theft/dismantling protection	У ^л
Type of configuration	Laserdrue
Product type:	product type: B.
Safety	
Protection index IP	IP2
Halogen free	I
- with dismantling protection	
Use conditions	
Operating temperature	-545
Identification	
Application, usage	KNX - operating system
Product family	product family: push-butte
Main design line	KNX - Berker B.

Berker B.IQ, KNX

Secondary design line(s)