

75164099

IP20

Fixing mode	flush-mountin
Technical version	4gar
Functions	
With room temperature controller	r
- for switch, push-button, dimmer and shutter function	ns
Compatibility	
- extension unit for light scene push-button	
Controls and indicators	
With LED indication	у
Number of buttons	
Measurement	
- dimming / position value transmitter 1 byte	
Screen	
With display	ſ
Materials	
Colour of labelling	105,105,10
Colour of design line	polar whi
Colour	polarwhi
RAL colour	RAL 9010 - Pure whi
Material	thermoplast
Surface appearance	ma
Type of surface treatment	untreate
Material family	Plast
Dimensions	
Dimensions Height	118,1 m
Height	118,1 m 88,5 m
Height Width	
Height Width LED control	88,5 m
Height Width <b>LED control</b> LED	88,5 m
Height Width LED control LED Connection	88,5 m

B.IQ push-button 4gang KNX - Berker B.IQ, polar white matt

Inscribable, with labelling field	r
<ul> <li>for installation in single standard wall boxes</li> <li>for plastic frames in the same "style" for additional applications, see the Design line B.7</li> <li>for additional products to complement the installation in matching colours/materials, refer to the Des platform S.1/B.x</li> </ul>	
Equipment	
Number of actuation points	
With anti-theft/dismantling protection	y
Type of configuration	Laserdru
Product type:	product type: B.
Safety	
Protection index IP	IP
Halogen free	
- with dismantling protection	
Use conditions	
Operating temperature	-545

Application, usage	KNX - operating systems
Product family	product family: push-button
Main design line	KNX - Berker B.IQ
Secondary design line(s)	KNX, Berker B.IQ