



75162094

IP20

B.IQ push-button 2gang KNX - Berker B.IQ, Aluminium, aluminium anodised

Technical features

Architecture

Fixing mode	flush-mounting
Technical version	2gang

Functions

With room temperature controller	no
- for switch, push-button, dimmer and shutter functions	

Compatibility

- extension unit for light scene push-button

Controls and indicators

With LED indication	yes
Number of buttons	2

Measurement

- dimming / position value transmitter 1 byte

Screen

With display	no
--------------	----

Materials

Colour of design line
Colour
RAL colour
Material / workmanship
Material
Surface appearance
Type of surface treatment
Material family

Dimensions

Depth	16,65 mm
Assembling height	16,7 mm
Height	88,5 mm
Width	88,5 mm

LED control

LED	with blue operation LED and 4 white status LEDs
	(labelling field illumination)

Connection

- for bus coupling unit flush-mounted



KNX, Berker B.IQ

Scope	of	del	liver	۷
-------	----	-----	-------	---

Secondary design line(s)

Scope of delivery	
Bus connection included	no
Accessories included	
Inscribable, with labelling field	no
 for installation in single standard wall boxes for additional products to complement the installation in matching platform S.1/B.x for aluminium frames in the same "style" for additional application 	-
Equipment	
Number of actuation points	4
With anti-theft/dismantling protection	yes
Product type:	product type: B.IQ
Safety	
Protection index IP	IP20
Halogen free	no
- with dismantling protection	
Use conditions	
Operating temperature	-545 °C
Identification	
Application, usage	KNX - operating systems
Product family	product family: push-button
Main design line	KNX - Berker B.IQ