



75161093

IP20

B.IQ push-button 1gang KNX - Berker B.IQ, Stainless steel, metal brushed

Technical features

Architecture

Fixing mode	flush-mounting
Technical version	1gang

Functions

With room temperature controller	no
- for switch, push-button, dimmer and shutter functions	

Compatibility

- extension unit for light scene push-button

Controls and indicators

With LED indication	yes
Number of buttons	1

Measurement

- dimming / position value transmitter 1 byte

Screen

With display	no
--------------	----

Materials

Colour of design line	Stainless steel
Colour	stainless steel
RAL colour	RAL 9022 - Pearl light grey
Material / workmanship	metal brushed
Material	stainless steel
Surface appearance	matt
Type of surface treatment	brushed

Dimensions

Assembling height	16,7 mm
Height	88,5 mm
Width	88,5 mm

LED control

LED	with blue operation LED and 2 white status LEDs (labelling field illumination)
-----	--

Connection

- for bus coupling unit flush-mounted

Scope of delivery

Bus connection included	no
-------------------------	----

Accessories included

Inscribable, with labelling field	no
- for installation in single standard wall boxes	
- for stainless steel frames in the same "style" for additional applications, see the Design line B.7	
- for additional products to complement the installation in matching colours/materials, refer to the Design platform S.1/B.x	

Equipment

Number of actuation points	2
With anti-theft/dismantling protection	yes
Product type:	product type: B.IQ

Safety

Protection index IP	IP20
Halogen free	no
- with dismantling protection	

Use conditions

Operating temperature	-5...45 °C
-----------------------	------------

Identification

Application, usage	KNX - operating systems
Product family	product family: push-button
Main design line	KNX - Berker B.IQ
Secondary design line(s)	Berker B.IQ, KNX