

75162093

IP20

B.IQ push-button 2gang KNX - Berker B.IQ, Stainless steel, metal brushed

Technical features

Fixing mode	flush-mounting
Technical version	2gang
Functions	
With room temperature controller	nc
- for switch, push-button, dimmer and shutter functions	
Compatibility	
 extension unit for light scene push-button 	
Controls and indicators	
With LED indication	yes
Number of buttons	2
Measurement	
- dimming / position value transmitter 1 byte	
Screen	
With display	nc
Materials	
Colour of design line	Stainless stee
Colour	stainless stee
RAL colour	RAL 9022 - Pearl light grey
Material / workmanship	metal brushed
Material	stainless stee
Surface appearance	mati
Type of surface treatment	brushed
Material family	Metal

Dimensions

Depth	16,65 mm
Assembling height	16,7 mm
Height	88,5 mm
Width	88,5 mm

LED control

LED	with blue operation LED and 4 white status LEDs
	(labelling field illumination)

Connection

- for bus coupling unit flush-mounted



no

no

Scope of delivery

Bus connection included

Accessories included

Inscribable, with labelling field

- for installation in single standard wall boxes

- for stainless steel frames in the same "style" for additional applications, see the Design line B.7

for additional products to complement the installation in matching colours/materials, refer to the Design platform S.1/B.x

Equipment

Number of actuation points	4
With anti-theft/dismantling protection	yes
Product type:	product type: B.IQ

Safety

Halogen free	no
- with dismantling protection	

Use conditions

Operating temperature	-545 °C
-----------------------	---------

Identification

Application, usage	KNX - operating systems
Product family	product family: push-button
Main design line	KNX - Berker B.IQ
Secondary design line(s)	KNX, Berker B.IQ