



75163090

IP20

B.IQ push-button 3gang KNX - Berker B.IQ, glass polar white

Technical features

	ctu	

Fixing mode	flush-mounting
Technical version	3gang

Functions

With room temperature controller	no
- for switch, push-button, dimmer and shutter functions	

Compatibility

- extension unit for light scene push-button

Controls and indicators

With LED indication	yes
Number of buttons	3

Measurement

- dimming / position value transmitter 1 byte

Screen

no

Materials

Colour of design line	glass polar white	
Colour	polarwhite	
RAL colour	RAL 9010 - Pure white	
Material	glass	
Surface appearance	glossy	
Type of surface treatment	Painted	
Material family	Glass	

Dimensions

Assembling height	16,7 mm
Height	88,5 mm
Width	88.5 mm

LED control

LED	with blue operation LED and 6 white status LEDs
	(labelling field illumination)

Connection

- for bus coupling unit flush-mounted

Scope of delivery

Bus connection included	no
-------------------------	----



Accessories included

Inscribable, with labelling field	no
 for installation in single standard wall boxes for glass frames in the same "style" for additional applications, see for additional products to complement the installation in matching platform S.1/B.x 	
Equipment	
Number of actuation points	6
With anti-theft/dismantling protection	yes
Product type:	product type: B.IQ
Safety	
Protection index IP	IP20
Halogen free	no
- with dismantling protection	
Use conditions	
Operating temperature	-545 °C
Identification	
Application, usage	KNX - operating systems
Product family	product family: push-button
Main design line	KNX - Berker B.IQ
Secondary design line(s)	Berker B.IQ, KNX