




4416



IP44

Change-over switch 2pole with imprint flush-mounted for lock cylinders with screw terminals, Die-Cast IP44

Technical features

Architecture

Type of control unit	Key
Fixing mode	flush-mounting

Configuration

- 2-pole off/change-over

Controls and indicators

- No

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC

Electric current

Switching current	16 A
-------------------	------

Cover, door

Dimensions aluminium cover plate (W x H)	100 x 125 mm
--	--------------

Materials

Material	Plastic/metal
----------	---------------

Dimensions

Depth	67 mm
Insertion depth	73 mm
Installation depth x Ø	73 x 65 mm
Contact spacing	> 3 mm
Diameter	65 mm
Height	125 mm
Width	100 mm

Installation, mounting

Installation mode	for screw fastening
-------------------	---------------------

Connection

Type of connection	Screw connection
- with screw terminals	

Cable

- with cable entry diameter 22.5 mm (PG 16) at bottom

Accessories included

- with flush-mounted box

Use	
Differentiation characteristic 3 - Sales	with screw terminals
Safety	
Protection index IP	IP44
Interlock	with cover lock
Identification	
Application, usage	Surface-mounted wet-room installation
Main design line	Die-Cast IP44